



NET-1000TW / 1500TW

NET-500TW / 750TW

FEATURES

- Ideal for network equipment, NAS, ATM, and Kiosks
- Line-interactive UPS with sine wave output
- Cost-efficient solution without compromising the performance
- High conversion efficiency (>95%) results in energy saving
- Automatic boost and buck voltage regulation
- LCD graphic display gives comprehensive information at a glance
- Rapid charge allows the batteries to reach 90% in 3 hours
- Compact design and easy to install
- Auto restart while AC is recovering
- Easy battery replacement



APPLICATIONS

- Midsize Servers
- ATM Machines
- Telecom & Networking
- Slot Machine



POWERNET LINE INTERACTIVE UPS SPECIFICATION

MODEL	NET-500TW	NET-750TW	NET-1000TW	NET-1500TW
Capacity	500VA / 350W	750VA / 450W	1000VA / 700W	1440VA / 900W
INPUT				
Voltage	100 / 110 / 120 or 220 / 230 / 240VAC			
Voltage Range	96-144VAC or 184-276VAC			
Nominal Frequency	50 or 60Hz (auto sensing)			
OUTPUT				
Voltage	100 / 110 / 120 or 220 / 230 / 240VAC			
Regulation	-10% to +6%			
Frequency	50 or 60Hz (auto sensing)			
Transfer Time	2~6ms (typical)			
Waveform	Pure sine wave			
Outlets	8 Outlets (battery backup + surge)			
BATTERY				
Battery Type & Quantity	12V / 7Ah x 1	12V / 9Ah x 1	12V / 7Ah x 2	12V / 9Ah x 2
Backup Time (Typical PC Load)	Up to 43 minutes	Up to 52 minutes	Up to 78 minutes	Up to 116 minutes
Recharge Time	3 hours to 90%			
MANAGEMENT				
USB Interface	for Windows® 2003 / 2008 / XP / Vista / 7 / 8 / 10			
PHYSICAL				
Dimension (D x W x H) (mm / in)	240 x 150 x 209 / 9.4 x 5.9 x 8.2		340 x 150 x 209 / 13.3 x 5.9 x 8.2	
Net Weight (kg / lb)	6.4 / 14.1	6.8 / 15.0	10.8 / 23.8	11.5 / 25.3